TRANSPARENT ACCESS AUTHENTICATION IN GPRS CORE NETWORKS

5 The present invention relates to a method and system for
transparent access authentication in 2G and 2.5G Mobile
Access Networks. This includes communication networks of the
GSM-, GPRS- and UMTS-standard well known to skilled persons.

10 In standardisation of Universal Mobile Telecommunication
System (UMTS Rel.5) comprehensive means are foreseen to
perform authentication on the application layer with no need
to interwork with the underlying radio and transport
networks. The mechanisms are based on the assumption that a
15 specific environment is prepared for deployment of IP
Multimedia Subsystem (IMS) services. It includes the use of
IMS SIM (ISIM) application, which in turn requires
Rel.99UICC's in the connected end devices to handle the
authentication and key agreement (AKA).
20 In case of deployment of IMS and IMS based services in a
network environment which is characterised by the use of SIM
cards, the standardised authentication mechanism will not be
applicable.

25 It is the object of the invention to provide method and
system for transparent access authentication which allow it
to run authentication transparently to the end device,
without requiring proprietary extensions and functions on
network or client side.

30

This object is achieved by providing a method and system
as described in the independent claims.

Other features which are considered to be characteristic
for the invention are set forth in the dependent claims.

The present invention describes a method for application
5   layer authentication of subscribers, connected to the
authenticating network domain by a 2G or 2.5G General Packet
Radio Service (GPRS) core network or a 3G UMTS network. The
authentication will be based on data which is assembled by
the network layer during establishment of a PDP context in
10   GPRS networks. This information is secured by standard SIM
card application. As the same mechanisms are used for
authentication in 3G networks, the further described
mechanism is also applicable there. No standard would be
touched in any way while using a 2G or 2.5G access network,
15   because no authentication on application layer is foreseen in
the standard. For UMTS Rel.5 standards and following, the
standard foresees specific methods. The use of the further
described method would be possible, although the standardised
authentication mechanism needs to be switched off. Switching
20   off the standardised authentication mechanism could be
interpreted as standard sensitive, but subsequent use of the
further described mechanism would be standard compliant
again.
Further, a migration path to UMTS Rel.5 standardised
25   authentication and the concept for parallel use of both
mechanisms is described.

The invention will now be described in further detail with
reference to the drawings.
30

Figure 1 depicts the general architecture of the system for
carrying out the invention;

Figure 2 depicts an embodiment of the invention with migration to IMS compliant architecture.

With reference to Figure 1, during PDP context establishment
5   the Serving GPRS Support Node (SGSN) is authenticating the
subscriber using the A3/A8 algorithm based on the end devices
SIM card in case of GSM and 2.5G GPRS and EDGE access
network.

The Gateway GPRS Support Node 1 (GGSN) receives a context
10 creation request and queries a Radius (Registration) server 2
(Remote Authentification Dial-In User Service) to get an IP
address assigned for the particular PDP context. Within the
context the Radius server 2 receives the MSISDN and/or the
IMSI of the subscriber. So in the session database 3 of the
15 Radius server 2 there is stored for each PDP context a pair
of IP address and IMSI/MSISDN. Based on the tunnel endpoint
ID (TEID) the GGSN 1 filters all packets running through the
PDP context once established, for the correct IP source
address. This means the GGSN 1 checks matching TEID/IP
20 address pairs, thus preventing falsification of source
addresses and so called "IP spoofing" for the complete
lifecycle of the PDP context. The TEID unambiguously
identifies a tunnel endpoint in the receiving GTP-U (GPRS
Tunnelling Protocol - User) or GTP-C (GPRS Tunnelling
25 Protocol - Control) protocol entity. The receiving side of a
GTP tunnel locally assigns the TEID value for the
transmitting side to use. The TEID values are exchanged
between tunnel endpoints using GTP-C messages (or RANAP
(Radio Access Network Application Part) in the UTRAN (UMTS
30 terrestrial Radio Access Network
In the application domain a subscriber database 4 exists that
stores all PubIDs the subscriber is using in the domain,
referring it to his PrivID, which is unique in the respective

application domain. The PrivID is correlated with an MSISDN
and/or IMSI.

In the request the user gives his PrivID for registration.
Upon receiving the registration request, the registration
5   proxy 5 queries the subscriber database 4 containing the
subscribers IDs (both public and private) together with the
MSISDN/IMSI. This data is stored in a table on the proxy
server platform.

Subsequently the proxy server 5 queries the session database
10   3 of the Radius server 2 in order to get the assigned IP
address of that session and the IMSI/MSISDN already
authenticated by the network's Home Location Register (HLR).
The authentication of the HLR guarantees further that the IP
address can be considered to be authenticated as well. Also
15   this information is stored in the table on the proxy server
platform.

Now the proxy server 5 starts the authentication procedure
according to the invention.
20

First, the proxy server 5 checks IMSI/MSISDN from Radius
server 2 database 3 and application domain database 4 for
match. If the pairs are not matching, the subscriber has
tried to register with an incorrect PrivID, which is not
25   correlated with his IMSI/MSISDN, if the pairs are matching
the next step is performed.

Second step is checking the subscribers IP address in the IP
network layer, meaning in the IP packet overhead field for
30   source address for match with the IP address assigned by the
Radius server 3. As the IP address was assigned to an
IMSI/MSISDN-authenticated session, also the IP address can be
considered as authenticated.

If the pairs are not matching, the subscriber used an incorrect IP address, if the pairs are matching the subsequent step is performed.

5 The proxy server 5 parses the application layer for IP addresses given in the headers of e.g. SIP registration message, SDP message bodies, etc and checks for match with the IP address in, which was already checked for match with the IP address assigned by the Radius server 2. If the pairs

10 are not matching the subscriber used incorrect signalling information, e. g. response addresses, etc. If the pairs are matching, the session setup can be considered as authenticated.

15 In all subsequent messages arriving at the proxy server 5, it checks for match of IP address in the IP packet overhead field for source address with that in the application layer protocol header fields and verifies the matching pairs against the IP address assigned by the Radius server 2.

20 If PubIDs are used in the following session, the PubIDs are checked against the PrivID which was stored in a table on the proxy server platform after querying the application domains database 4.

25 The described functionality gives the network operator the opportunity to run authentication transparently to the end device, without requiring proprietary extensions and functions on network or client side. In case of SIP based signalling, the migration to fully standard compliant UMTS

30 Rel.5 mechanisms and a strategy for parallel operation is necessary, this will be described now.

As the IMS domain as standardised for UMTS Rel.5 will include
its own authentication mechanism, it is necessary to support
a scenario where the subscribers are migrating to ISIM
enabled end devices. To exploit the benefits of the
5   standardised authentication mechanism, both mechanisms have
to be supported in parallel.
This is done by an additional function that checks each
incoming signalling message, first for the protocol, if it is
any other protocol than SIP, the session is routed to the
10   proxy server 5.

With reference to Figure 2, the same routing decision is taken
if the message is based on SIP, but the client does not
support standardised UMTS Rel.5 authentication. If the client
15   does support standardised authentication method, e.g. is ISIM
enabled, the message is routed to the standard compliant
Proxy Call State Control Function (P-CSCF). First trigger for
routing decisions is the protocol type, as described above.
Further triggers could be the key exchange mechanism used for
20   setting up the secured connection between UE and P-CSCF (if
the end device is starting key agreement, it can be
considered as standard compliant and the request is routed to
the P-CSCF), or other elements included in the UMTS Rel.5
header as well as any private extension, which is, however,
25   possible but not necessary. If trigger points available in
signalling should be insufficient, also database lookups can
be used to base routing decisions on.

The authentication procedure is as follows
30   First, a decision is required by which node P-CSCF 6 or proxy
server 5 the register shall be routed
For this, a routing module 7 is provided which will be the
standard entry point for all messages. The routing module 7

decides by evaluation of PrivID which node will handle the message. The routing module 7 refers to subdomains (e.g. user@gprs.tmo.de and user@tmo.umts.de) within the domain part of the Network Access Identifier (NAI), see 3GPP

5 specification 23.228. This requires that NAIs for 3G subscribers have to provide subdomains.

The routing module 7 shall set a routing entry, by using only the PrivID, subsequent messages shall be identified by the IP

10 source address listed in the routing table.
The routing module 7 identifies the responsible proxy function, i.e. proxy server 5 or P-CSCF 6, by evaluating the PrivID (URIs subdomains) This rises the request towards IMSI/MSISDN and URIs to be chosen according to this

15 functionality.
In case other protocols shall be used beside SIP, such as e.g. SMTP, HTTP, SOAP (.NET), etc, the proxy server 5 must be extended, and authenticate the subscribers by use of the IP address, subsequently resolving the IMSI/MSISDN and matching

20 of the particular identifier of the protocol, which is stored in the subscriber profile of the subscriber database 4. This requires the population of the subscriber profile with the required data elements and extension of the routing module to enable protocol dependent routing.

25

In case separate access networks are used, the application platform has to know which type of access network is used to adapt service delivery accordingly. This requires that a change request has to be stated against the SGSN to enable it

30 to send the access type to the GGSN which includes it in the radius request, so the access network type will be available in the session database 3. This enables all applications to

request the access network type and use it, e.g. for Quality
of Service (QoS) means.

Abbreviations

2.5G	second and half generation (e. g. GPRS, EDGE)
2G	second generation (e. g. GSM)
3G	third generation (e. g. UMTS)
AKA	authentication and key agreement
CC	Circuit Switched
IMS	IP multimedia subsystem
IMSI	International Mobile Subscriber Identity
ISIM	IMS SIM
MSISDN	Mobile Station ISDN Number
NAI	Network Access Identifier
P-CSCF	Proxy-Call-State-Control-Function
SIM (card)	(GSM) Subscriber Identity Module (card)
SIP	Session Initiation Protocol
TEID	Tunnel Endpoint ID
UE	User Equipment
UICC	UMTS IC Card
UMTS	Universal mobile telecommunication system
URI	Uniform Ressource Locator